



MATERIAL SAFETY DATA SHEET

Revised/ Reviewed: July 23, 2007

SLIDE™ SH (a.k.a. Slide™ SH Juniors)

An endodontic file lubricant to facilitate file movement within and debris removal from the root canal.

Section 1- Product and Company Information

Manufactured by: Miltex, Inc.; 589 Davies Drive, York, PA 17402

Information: 717-840-9335, 717-840-9347 (fax)

Chemical Name & Synonyms: 1,2,3-Propanetriol/ Sodium Hypochlorite

Chemical Formula: Poly alcohols/ Bleach/ Water

Section 2 – Composition/ Information on Ingredients

- Glycerin; CAS # 56-81-5; < 80% w/v; ACGIH TLV = 10 mg/m³
- Sodium Hypochlorite; CAS # 7681-52-9; < 0.1% w/v; no information on threshold limit
- The balance is material is water.

Section 3 - Health Identification

Potential Health Effects: Inhalation of mist or spray can cause respiratory distress. Allergic reaction possible from prolonged contact.

Primary Route(s) of Entry: Ingestion, Inhalation, and Skin Contact

Carcinogen: None of the materials components are known to be carcinogenic.

Medical Conditions Aggravated by Exposure: No information available

HMIS Ratings: Health = 1; Flammability = 1; Reactivity = 0; PPE = B

Section 4 - First Aid Measures

Seek medical attention for all cases of overexposure.

Eyes: Flush with tepid water for at least 15 minutes. Seek medical attention.

Skin: Remove any contaminated clothing. Wash affected area with soap and water.

Ingestion: Seek medical attention should complications develop.

Inhalation: Remove person to fresh air. As needed, seek medical attention.

Section 5 – Fire Fighting Measures

Flash Point (Test Method): 320°F (closed-cup)

Auto Ignition Temperature: No information available

Flammable Limits- No information available

Extinguishing Media: Use suitable for surrounding materials.

Special Fire Fighting Procedures: If necessary, wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: Hazardous when exposed to flames, heat, or oxidizers.

Section 6 - Physical and Chemical Properties

Physical State: Liquid at ambient temperature.

Appearance and Odor: A clear, colorless, viscous, gel-like liquid.

Melting Point (°C): Not applicable

Specific Gravity (H₂O=1): No information available, likely greater than 1.

Vapor Pressure (mm Hg): No information available

Vapor Density (Air=1): No information available

Evaporation Rate (butyl acetate=1): No information available

Solubility in Water: Soluble

pH: No information available

Section 7 – Stability and Reactivity

Stability: No information available, thought to be stable.

Conditions to Avoid: Heat and open flame

Incompatibility/ Materials to Avoid: Contact with strong oxidizing agents may cause explosion.

Hazardous Polymerization: No information available, believed that it would not occur.

Hazardous Decomposition Products: Carbon oxides and acrolein

Section 8 – Accidental Release, Disposal, and Ecological Information

Spill Response: Absorb with sand or vermiculite, scoop up and containerize for proper disposal.

Waste Disposal Method: Dispose of in accordance with all applicable federal, state, and local regulations.

Ecological, General: No information available

Section 9 – Exposure Controls/ Personal Protection

Eye Protection: Safety glasses or goggles

Respiratory Protection: None normally required. Wear self-contained breathing apparatus in high vapor areas.

Ventilation Recommendations: Local and general as needed.

Skin Protection: Impervious gloves

Other: As required to keep materials from eyes, skin, or clothing and from inhaling vapors.

Section 10 – Storage and Handling

Storage: Store in a cool, dry, well-ventilated area. Keep container tightly closed. Keep away from oxidizers, acids, and ignition sources.

Handling: Wash thoroughly after handling.

Section 11 – Miscellaneous

Toxicological Information: Glycerin LD₅₀ (oral, rat) = 12,600 mg/kg

Transportation Information: Material is not a U.S. DOT Hazardous Material

Other: --

Liability Disclaimer: MSDS information is provided based on OSHA's Hazardous Communication Regulation and for use of the persons required to receive this information under this regulation. The information is neither designed nor recommended for any other use or for use by any other person, including compliance with other laws. Miltex does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. Miltex does not warrant the accuracy or authenticity of this MSDS unless it has been obtained directly from Miltex or posted or viewed on a Miltex website. This MSDS is based on information that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under Miltex's control, each user is responsible for making their own determination as to the safe and proper handling of this material in their own particular use of this material. Miltex makes no representation or warranty, either express or implied, including as to merchantability or fitness for a particular purpose.